

a:		A:	A
b:	ᵇ	B:	B
c:		C:	C
d:	ᵈ	D:	D
e:		E:	E
f:	ᶠ	F:	F
g:		G:	G
h:	ᵃ	H:	H
i:	ᵇ	I:	I
j:	ᶜ	J:	J
k:	ᵈ	K:	K
l:	ᵉ	L:	L
m:	ᶠ	M:	M
n:	ᶡ	N:	N
p:	ᶢ	P:	P
q:	ᶣ	Q:	Q
r:	ᶤ	R:	R
<:	ᶥ	S:	S
>:	ᶦ	T:	T
x:	ᶧ	U:	U
	ᶨ	V:	V
	ᶩ	W:	W
	ᶪ	X:	X
	ᶫ	Y:	Y
	ᶬ	Z:	Z
	ᶭ	[unconnected]	.

Small numbers as themselves:

1 2 3 4 5 6 7 8 9 0

Larger numbers (5x7) as 'capital numbers:

i.e. '!' through ')', respectively

! @ # \$ % ~ & * ()

top
left
bottom
right

These characters define connection points in component definitions

Pieces of 16 pin packages

8/09/78

'unconnected' pin

This figure shows the available characters in "Gates32.al"
 These characters are normally read in by SIL as FONT 3

(this picture is available as <SIL>GATES

XEROX	Project	Reference	File	Designer	Rev	Date	Page
PARC	S I L	Gates Symbols	Gates32.sil	R Bates	A	7/12/79	31