HEADLINE documentation

D. Austin Henderson, Jr.
Last revised: August 5, 1982

<LISPUSERS>HEADLINE (and **.DCOM**) contains three functions for manipulating windows which contain headlines ("headline windows").

HEADLINE (PHRASE FONT POSITION ALIGNMENT)

Creates a headline window with   Phrase printed in font   Font at position   Position aligned as per Alignment; the window is just large enough to hold the headline.   Phrase is any Lisp object.   Font defines a font as per FONTCREATE (eg. (TIMESROMAN 18 BOLD)); if NIL, TimesromanD 36 is used. Position is a position giving the reference point for placing the window; if NIL, the user is given a chance to position the window with MOVEW. If   Postion is given,   Alignment gives the alignment of the window with respect to   Position as (xalignment . yalignment) where xalignment is one of LEFT, CENTER, or RIGHT and yalignment is one of BOTTOM, CENTER, or TOP; for convenience, if Position is CENTER then it is taken to mean (CENTER . CENTER), etc.

BILLBOARD (TITLES ALIGNMENT SEPARATION POSITION)

Creates a set of vertically arranged headline windows.   Titles is a list of (phrase font) sublists where phrase and font are as in Headline.   Alignment is one of LEFT, CENTER, or RIGHT, indicating how the windows are aligned with each other; defaults to CENTER.   Separation indicates the spacing between the bottoms of the windows; defaults to 70.   Position indicates where the top (first) of the windows is to appear; defaults to somewhere near the top center of the screen.

CLOSEHEADLINES ( )

Closes all the active headline windows.